

HC-STA-B32-BWD-ELC-AL - Housing



1424845

<https://www.phoenixcontact.com/in/products/1424845>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Panel mounting base B32, with double locking latch, material: Die-cast aluminum, salt water resistant, height: 32.4 mm, cable gland: none, Standard, with flat gasket

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial Data

Item number	1424845
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF7
Product Key	BF7APB
Catalog Page	Page 644 (C-2-2019)
GTIN	4055626382500
Weight per Piece (including packing)	185.5 g
Weight per Piece (excluding packing)	180 g
Customs tariff number	85389099
Country of origin	CN

1424845


<https://www.phoenixcontact.com/in/products/1424845>

Technical Data

Product properties

Type	B32
Product type	Housing with locking latch
Application	Standard
Housing type	Panel mounting base
Locking type	with double locking latch
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	91.7 mm
Height	32.4 mm
Length	123 mm
Drill hole distance, horizontal	110 mm
Drill hole distance, vertical	65 mm
Hole diameter	5.5 mm

Installation dimensions

Width of the assembly cutout	71 mm
Length of the assembly cutout	86 mm

Material specifications

Color	gray aluminum
Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR, conductive NBR, conductive
Housing surface material	uncoated
Locking latch material	PA
Impact strength	IK09
Housing material	Die-cast aluminum, salt water resistant

Mechanical properties

Mechanical data

Locking type	Latch
--------------	-------

Environmental and real-life conditions

Ambient conditions

	IP66
--	------

HC-STA-B32-BWD-ELC-AL - Housing



1424845

<https://www.phoenixcontact.com/in/products/1424845>

Degree of protection	IP67
	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in