

# OPT- 5DC/ 48DC/100 - Miniature solid-state relay



2967992

<https://www.phoenixcontact.com/in/products/2967992>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Plug-in miniature solid-state relay, input solid-state relay, 1 N/O contact, input voltage: 5 V DC



## Your advantages

- Vibration and shock resistant
- RT III-proof (wash-proof)
- Wear-free and durable
- Zero voltage switch at AC output
- Switching power of up to 24 V DC/5 A
- Can be soldered on PCB

## Commercial Data

Item number	2967992
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK61F2
Catalog Page	Page 396 (C-5-2019)
GTIN	4017918820749
Weight per Piece (including packing)	4.9 g
Weight per Piece (excluding packing)	4.9 g
Customs tariff number	85364190
Country of origin	HU

# OPT- 5DC/ 48DC/100 - Miniature solid-state relay



2967992

<https://www.phoenixcontact.com/in/products/2967992>

## Technical Data

### Product properties

Product type	Single solid-state relay
Operating mode	100% operating factor

### Insulation characteristics

Insulation	Basic insulation
------------	------------------

### Insulation characteristics: Standards/regulations

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	2

### Electrical properties

Maximum power dissipation for nominal condition	0.02 W
Test voltage (Input/output)	2.5 kV (50 Hz, 1 min., input/output)

### Input data

Nominal input voltage $U_N$	5 V DC
Input voltage range in reference to $U_N$	0.8 ... 1.2
Input voltage range	4 V DC ... 6 V DC
Switching threshold "0" signal, voltage	$\leq 0.8$ V
Switching threshold "1" signal voltage	$\geq 2.5$ V
Typical input current at $U_N$	4 mA
Typical response time	20 $\mu$ s (at $U_N$ )
Typical turn-off time	300 $\mu$ s (at $U_N$ )
Transmission frequency	300 Hz

### Output data

Contact type	1 N/O contact
Design of digital output	electronic
Output voltage range	3 V DC ... 48 V DC
Limiting continuous current	100 mA
Voltage drop at max. limiting continuous current	$\leq 1$ V
Output circuit	2-conductor, floating
Protective circuit	Reverse polarity protection Surge protection

### Dimensions

Width	5 mm
Height	28 mm
Depth	15 mm

### Environmental and real-life conditions

# OPT- 5DC/ 48DC/100 - Miniature solid-state relay



2967992

<https://www.phoenixcontact.com/in/products/2967992>

## Ambient conditions

Degree of protection	RT III
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

## Approvals

### Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

## Standards and regulations

### Standards/regulations

Standards/regulations	IEC 60664
	EN 50178

## Mounting

Assembly instructions	in rows with zero spacing
Mounting position	any

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)