SF-20KP023 - Crimp contact



https://www.phoenixcontact.com/in/products/1621581



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: $2.5~\text{mm}^2$... $4~\text{mm}^2$, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244465

Your advantages

- · Crimping connection: vibration- and temperature-resistant assembly
- · High tensile strength of the connection
- · Low contact resistance
- · Easy production monitoring

Commercial Data

Item number	1621581
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	ABR
Product Key	ABREBD
Catalog Page	Page 121 (C-2-2019)
GTIN	4046356937214
Weight per Piece (including packing)	1.091 g
Weight per Piece (excluding packing)	1.004 g
Customs tariff number	85366990
Country of origin	DE

SF-20KP023 - Crimp contact



https://www.phoenixcontact.com/in/products/1621581



Technical Data

Mounting

	Connection method	Crimp connection
Product properties		
	Product type	Crimp contact
	Contact type	turned
	Series	SF

Connection data

Connection method	Crimp connection
Type of contact	Pin
Conductor cross section	2.5 mm² 4 mm²

Material specifications

Contact surface	Nickel-plated (Ni), with gold coating (Au)
Contact material	CuZn

Dimensions

Mechanical	characteristics
Miconanioai	or iai aotor iotios

Contact diameter	2 mm
------------------	------

Mechanical properties

Mechanical data

echanical data	
Insertion/withdrawal cycles	100

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in