

REL-PR-BL-24AC/4X21 - Single relay



1157979

<https://www.phoenixcontact.com/in/products/1157979>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in power relay, basic version, Plug-in connection, 4 changeover contacts, status display: Green LED, Input voltage: 24 V AC

Commercial Data

Item number	1157979
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6193
GTIN	4063151163839
Weight per Piece (including packing)	73.83 g
Weight per Piece (excluding packing)	70 g
Customs tariff number	85364190
Country of origin	CN

REL-PR-BL-24AC/4X21 - Single relay



1157979

<https://www.phoenixcontact.com/in/products/1157979>

Technical Data

Notes

General	The outputs are not suitable for switching different outer conductors.
General	Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.

Product properties

Product type	Single relay
Operating mode	100% operating factor
Mechanical service life	approx. 10^7 cycles

Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	2

Electrical properties

Maximum power dissipation for nominal condition	2.3 W
Test voltage (Winding/contact)	2 kV _{rms} (50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact)	2 kV _{rms} (50 Hz, 1 min., changeover contact/changeover contact)
Test voltage ()	1 kV _{rms} (50 Hz, 1 min., open contact)

Air clearances and creepage distances between the power circuits

Rated insulation voltage	250 V AC
Rated surge voltage	4 kV

Input data

Coil side

Nominal input voltage U_N	24 V AC
Input voltage range	19.2 V AC ... 26.4 V AC (20 °C)
Mains frequency	50/60 Hz
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at U_N	2.3 mA (50 Hz)
Typical response time	≤ 20 ms (depending on phase relation)
Typical release time	≤ 20 ms (depending on phase relation)
Status display	Green LED

Output data

Switching

Contact switching type	4 changeover contacts
Type of switch contact	Single contact

REL-PR-BL-24AC/4X21 - Single relay



1157979

<https://www.phoenixcontact.com/in/products/1157979>

Contact material	AgSnO
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	17 V (10 mA)
Limiting continuous current	10 A
Min. switching current	10 mA (17 V)
Interrupting rating (ohmic load) max.	240 W (24 V DC)
	150 W (48 V DC)
	120 W (60 V DC)
	100 W (110 V DC)
	100 W (220 V DC)
	2500 VA
Switching capacity min.	17 mW

Connection data

Connection method	Plug-in connection
-------------------	--------------------

Dimensions

Width	41.5 mm
Height	28 mm
Depth	36.5 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection (Relay)	RT I
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Altitude	≤ 2000 m

Standards and regulations

Standards/regulations	EN 61810
-----------------------	----------

Air clearances and creepage distances between the power circuits

Standards/regulations	IEC 60664
-----------------------	-----------

Mounting

Mounting type	Plug-in mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

REL-PR-BL-24AC/4X21 - Single relay



1157979

<https://www.phoenixcontact.com/in/products/1157979>

Mandatory Accessories

ECOR-4-BSC2/4X21 - Relay base

1157947

<https://www.phoenixcontact.com/in/products/1157947>

ECOR-4 relay base, for power relay with 4 changeover contacts, ring cable lug screw connection, for mounting on NS 35/7.5



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in