

HC-A3-STQ1,5-KML-G-PA - Connector



1641604

<https://www.phoenixcontact.com/in/products/1641604>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



HEAVYCON QUICKON coupling housing A3, for single locking latch, 3-pos., with PE connection, plug, QUICKON connection, straight cable outlet

Commercial Data

Item number	1641604
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF7
Product Key	BF7AJX
Catalog Page	Page 505 (C-2-2019)
GTIN	4017918890001
Weight per Piece (including packing)	35.4 g
Weight per Piece (excluding packing)	35.2 g
Customs tariff number	85366990
Country of origin	PL

HC-A3-STQ1,5-KML-G-PA - Connector

1641604

<https://www.phoenixcontact.com/in/products/1641604>

Technical Data

Mounting

Mounting type	This product is only intended for use outdoors.
Assembly instructions	This product is only intended for use outdoors. If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Connection method	QUICKON fast connection


Product properties

Type	D7
Product type	Contact insert with a fixed no. of positions
Number of positions	3
Connection profile	3+PE
Contact numbering	1 - 3
Application	Standard
No. of cable outlets	1
Type	Male
Housing type	Complete housing
Locking type	with single locking latch
Series	HC-A
Shielded	no
Cable outlet	straight
Pg screw connection	with

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Dimensions

Dimensional drawing	
Width	34 mm
Height	62.8 mm
Length	26.5 mm
Wrench size, union nut	19 mm

HC-A3-STQ1,5-KML-G-PA - Connector



1641604

<https://www.phoenixcontact.com/in/products/1641604>

Electrical properties

Min. AWG, flexible, multi-strand	18
Rated voltage (III/3)	230 V (Conductor-PE)
Rated surge voltage (II/2)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (III/3)	4 kV
Rated surge voltage	4 kV
Rated current	10 A
rated voltage (II/2)	630 V
rated voltage (III/2)	320 V
Rated voltage (III/3)	230/400 V
	230 V (Conductor-PE)
	400 V (Conductor-Conductor)

Mechanical properties

Mechanical data

Locking type	Latch
Insertion/withdrawal cycles	>= 500

Material specifications

Material Housing	PA
Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-25 °C ... 80 °C
Temperature when conductor connected	-5 °C ... 50 °C (specifications of the cable manufacturer must also be observed)
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in