


# REL-MR- 60DC/21AU - Single relay



2961134

<https://www.phoenixcontact.com/in/products/2961134>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in miniature power relay, with multi-layer gold contact, 1 changeover contact, input voltage 60 V DC

## Your advantages

- Safe isolation according to DIN EN 50178 between coil and contact
- High degree of protection up to RT III depending on type (wash-proof)
- Power contacts up to 6 A

## Commercial Data

Item number	2961134
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6195
Catalog Page	Page 394 (C-5-2019)
GTIN	4017918130848
Weight per Piece (including packing)	6.984 g
Weight per Piece (excluding packing)	6.47 g
Customs tariff number	85364190
Country of origin	CZ

## Technical Data

### Product properties

Product type	Single relay
Set comprises	2966142 PLC-RSC- 60DC/21AU
	2966281 PLC-RSC-120UC/21AU
	2980034 PLC-RSC-125DC/21AU
	2966294 PLC-RSC-230UC/21AU
	2966294 PLC-RSC-230UC/21AU
	2966579 PLC-RSP- 60DC/21AU
	2966582 PLC-RSP-120UC/21AU
	2966647 PLC-RSP-230UC/21AU
	2900309 PLC-RPT- 60DC/21AU
	2900310 PLC-RPT-120UC/21AU
	2900311 PLC-RPT-230UC/21AU
	2966320 PLC-RSC-120UC/ 1AU/SEN
	2966333 PLC-RSC-230UC/ 1AU/SEN
	2967390 PLC-RSP-120UC/ 1AU/SEN
	2967413 PLC-RSP-230UC/ 1AU/SEN
	2900314 PLC-RPT-120UC/ 1AU/SEN
2900315 PLC-RPT-230UC/ 1AU/SEN	
2987066 PLC-RSP-110UC/21AU/RW	
2900323 PLC-RPT-110UC/21AU/RW	
Operating mode	100% operating factor
Mechanical service life	2x 10 <sup>7</sup> cycles

### Insulation characteristics

Overvoltage category	III
Pollution degree	3

### Electrical properties

Maximum power dissipation for nominal condition	0.18 W
Test voltage (Winding/contact)	4 kV AC (50 Hz, 1 min., winding/contact)

### Input data

#### Coil side

Nominal input voltage $U_N$	60 V DC
Input voltage range	36 V DC ... 165 V DC
Typical input current at $U_N$	3 mA
Typical response time	5 ms
Typical release time	2.5 ms
Coil resistance	20500 $\Omega$ $\pm$ 15 % (at 20 °C)

# REL-MR- 60DC/21AU - Single relay



2961134

<https://www.phoenixcontact.com/in/products/2961134>

## Output data

### Switching

Contact type	1 changeover contact
Type of switch contact	Single contact
Drive and function	monostable
Drive (polarity)	bipolar
Contact material	AgSnO, hard gold-plated
Maximum switching voltage	30 V AC 36 V DC
Minimum switching voltage	100 mV (at 10 mA)
Limiting continuous current	50 mA
Maximum inrush current	50 mA
Min. switching current	1 mA (at 24 V)
Interrupting rating (ohmic load) max.	1.2 W (at 24 V DC)

### Switching: when the gold layer is destroyed

Note	the following values are applicable if a gold layer is destroyed
Contact material	AgSnO
Maximum switching voltage	250 V AC
Minimum switching voltage	5 V (at 100 mA)
Limiting continuous current	6 A
Min. switching current	10 mA (at 12 V)
Interrupting rating (ohmic load) max.	140 W (at 24 V DC) 20 W (at 48 V DC) 18 W (at 60 V DC) 23 W (at 110 V DC) 40 W (at 220 V DC) 1500 VA (for 250 V AC)
Switching capacity	2 A (at 24 V, DC13) 0.2 A (at 110 V, DC13) 0.1 A (at 220 V, DC13) 3 A (at 24 V, AC15) 3 A (at 120 V, AC15) 3 A (at 230 V, AC15)

## Connection data

Connection method	Plug / solder connection
-------------------	--------------------------

## Dimensions

# REL-MR- 60DC/21AU - Single relay



2961134

<https://www.phoenixcontact.com/in/products/2961134>

Dimensional drawing	
Width	5 mm
Height	28 mm
Depth	15 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	RT III
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

## Approvals

### Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group EN 60068-2-60
----------------	---

## Standards and regulations

Standards/regulations	IEC 60664 EN 50178 EN 61810-1
-----------------------	-------------------------------------

## Mounting

Assembly instructions	in rows with zero spacing
Mounting position	any

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)