

ECOR-4-BSC2/4X21 - Relay base



1157947

<https://www.phoenixcontact.com/in/products/1157947>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

ECOR-4 relay base, for power relay with 4 changeover contacts, ring cable lug screw connection, for mounting on NS 35/7.5



Commercial Data

Item number	1157947
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6314
GTIN	4063151163907
Weight per Piece (including packing)	80.93 g
Weight per Piece (excluding packing)	80.93 g
Customs tariff number	85366990
Country of origin	CN

Technical Data

Notes

Notes on operation	Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.
Notes on operation	The outputs are not suitable for switching different outer conductors with appropriate switching output (applies to the AC optocoupler variants and relays).
Notes on safety	The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.
Assembly instruction:	At least a basic level of insulation is maintained against adjacent modules in the DIN rail direction. If the application has higher requirements on the insulation (reinforced insulation), then these must be realized through suitable measures (e.g. partition plates).
Assembly instruction:	Any unused screw connections have to be tightened with torque.

Product properties

Product family	ESSENTIAL edition
Operating mode	100% operating factor

Insulation characteristics

Insulation	Basic insulation
------------	------------------

Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	2

Electrical properties

Air clearances and creepage distances between the power circuits

Rated insulation voltage	250 V AC
Rated surge voltage	4 kV

Input data

Nominal input voltage U_N	≤ 230 V AC/DC
-----------------------------	--------------------

Connection data

Connection method	Screw connection
Conductor cross section rigid	0.5 mm ² ... 2.5 mm ²
Conductor cross-section rigid (2 conductors with same cross section)	0.5 mm ² ... 2.5 mm ² (with ferrule)
Conductor cross section flexible	0.5 mm ² ... 2.5 mm ²
Conductor cross section flexible (2 conductors with same cross section)	0.5 mm ² ... 2.5 mm ² (with ferrule)
Tightening torque	1.2 Nm

ECOR-4-BSC2/4X21 - Relay base



1157947

<https://www.phoenixcontact.com/in/products/1157947>

Dimensions

Width	44.1 mm
Height	83.3 mm
Depth	30 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 ()
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m

Standards and regulations

Air clearances and creepage distances between the power circuits

Standards/regulations	DIN EN 50178
-----------------------	--------------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in