

ST-10KS035 - Crimp contact



1618464

<https://www.phoenixcontact.com/in/products/1618464>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Crimp contact, Socket, turned, contact diameter: 1 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1243216

Your advantages

- Crimping connection: vibration- and temperature-resistant assembly
- High tensile strength of the connection
- Low contact resistance
- Easy production monitoring

Commercial Data

Item number	1618464
Packing unit	100 pc
Minimum order quantity	100 pc
Sales Key	ABR
Product Key	ABREBC
Catalog Page	Page 70 (C-2-2019)
GTIN	4055626053516
Weight per Piece (including packing)	0.248 g
Weight per Piece (excluding packing)	0.22 g
Customs tariff number	85366990
Country of origin	DE

ST-10KS035 - Crimp contact



1618464

<https://www.phoenixcontact.com/in/products/1618464>

Technical Data

Mounting

Connection method	Crimp connection
-------------------	------------------

Product properties

Product type	Crimp contact
Contact type	turned
Series	ST


Connection data

Connection method	Crimp connection
Type of contact	Socket
Conductor cross section	0.25 mm ² ... 1 mm ²

Material specifications

Contact surface	Nickel-plated (Ni), with gold coating (Au)
Contact material	CuZn

Dimensions

Dimensional drawing	
Length	13.1 mm

Mechanical characteristics

Contact diameter	1 mm
------------------	------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	100
-----------------------------	-----

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in