# HC-STA-D07-SHCWS-1STP11-EL-AL - Housing



1419241

https://www.phoenixcontact.com/in/products/1419241

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Box mounting bases D7, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x Pg11, height: 27.9 mm, cable gland: none, Standard, enclosed bottom

#### **Commercial Data**

Item number	1419241
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF7
Product Key	BF7APF
Catalog Page	Page 517 (C-2-2019)
GTIN	4055626159874
Weight per Piece (including packing)	39.7 g
Weight per Piece (excluding packing)	39.5 g
Customs tariff number	85389099
Country of origin	CN

# HC-STA-D07-SHCWS-1STP11-EL-AL - Housing



1419241

https://www.phoenixcontact.com/in/products/1419241

## **Technical Data**

#### Notes

General	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05,
	Q07, Q12

#### Product properties

Туре	D7
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	1
Type of the screw connection	1x Pg11
Housing type	Box mounting bases
Locking type	with single locking latch
Shielded	no
Cable outlet	lateral
Pg screw connection	none

#### **Dimensions**

Dimensional drawing	38 41 28 30 30 32 342 20 342 2
Width	38 mm
Height	27.9 mm
Length	24.2 mm
Hole diameter	3.2 mm

#### Material specifications

Color	gray aluminum
Flammability rating according to UL 94	V0 (Interlock)
Housing surface material	uncoated
Locking latch material	PA
Impact strength	IK06
Housing material	Die-cast aluminum, salt water resistant

### Mechanical properties

#### Mechanical data

Type of the screw connection	1x Pg11
Locking type	Latch

## Environmental and real-life conditions

# HC-STA-D07-SHCWS-1STP11-EL-AL - Housing



1419241

https://www.phoenixcontact.com/in/products/1419241

#### Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in