SF-7QP2000 - Crimp contact

1605639

https://www.phoenixcontact.com/in/products/1605639



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Crimp contact, Pin, turned, Single contact, contact diameter: 2 mm, crimp range: 1 mm² ... 2.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241953

Your advantages

- · Crimping connection: vibration- and temperature-resistant assembly
- High tensile strength of the connection
- · Low contact resistance
- · Easy production monitoring

Commercial Data

Item number	1605639
Packing unit	50 рс
Minimum order quantity	50 pc
Sales Key	ABR
Product Key	ABREBD
Catalog Page	Page 160 (C-2-2019)
GTIN	4046356182270
Weight per Piece (including packing)	0.976 g
Weight per Piece (excluding packing)	0.918 g
Customs tariff number	85366990
Country of origin	DE

SF-7QP2000 - Crimp contact

1605639

https://www.phoenixcontact.com/in/products/1605639



Technical Data

lounting	
Connection method	Crimp connection
roduct properties	
Product type	Crimp contact
Contact type	turned
Series	SF
onnection data	
Connection method	Crimp connection
Type of contact	Pin
Conductor cross section	1 mm ² 2.5 mm ²
laterial specifications	
Contact surface	Nickel-plated (Ni), with gold coating (Au)
Contact material	CuZn
imensions	
Dimensional drawing	
Length	25.2 mm
Mechanical characteristics	
Contact diameter	2 mm
lechanical properties	
Mechanical data	
Insertion/withdrawal cycles	100

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in