

# RIF-1-BPT/2X21 - Relay base



2900931

<https://www.phoenixcontact.com/in/products/2900931>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Relay base RIF-1..., for miniature power relay with 1 or 2 changeover contacts or solid-state relays of the same design, Push-in connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

## Commercial Data

Item number	2900931
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6522
Catalog Page	Page 288 (C-5-2019)
GTIN	4046356733151
Weight per Piece (including packing)	49.1 g
Weight per Piece (excluding packing)	49.1 g
Customs tariff number	85366990
Country of origin	CN

# RIF-1-BPT/2X21 - Relay base



2900931

<https://www.phoenixcontact.com/in/products/2900931>

## Technical Data

### Notes

Notes on operation	FBS 2-6... plug-in bridge for the input side (A2) and FBS-2-8... plug-in bridge for the output side (11/21)
--------------------	---

### Product properties

Product family	RIFLINE complete
----------------	------------------

### Electrical properties

Nominal voltage $U_N$	250 V AC/DC
Nominal current $I_N$	max. 13 A (Depends on application/assembly)
Protective circuit	depending on the selected input/suppressor modules

### Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (Ferrule with plastic sleeve)
	0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (Ferrule with plastic sleeve, two conductors on double terminal block)
Conductor cross section AWG	26 ... 16 (solid)
	26 ... 16 (flexible)

### Dimensions

Width	16 mm
Height	96 mm
Depth Retaining bracket	75 mm (with retaining bracket)

### Drill hole

Diameter	3.2 mm
----------	--------

### Material specifications

Flammability rating according to UL 94	V2 (Housing)
--	--------------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (Depends on application/assembly)
Ambient temperature (storage/transport)	-40 °C ... 85 °C

### Approvals

#### Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
----------------	----------------------------

# RIF-1-BPT/2X21 - Relay base



2900931

<https://www.phoenixcontact.com/in/products/2900931>

	EN 60068-2-60
--	---------------

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)