SF-20KS023 - Crimp contact

1621578

https://www.phoenixcontact.com/in/products/1621578



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 2.5 mm² ... 4 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244462

Your advantages

- · Crimping connection: vibration- and temperature-resistant assembly
- High tensile strength of the connection
- · Low contact resistance
- · Easy production monitoring

Commercial Data

Item number	1621578
Packing unit	50 рс
Minimum order quantity	50 pc
Sales Key	ABR
Product Key	ABREBD
Catalog Page	Page 121 (C-2-2019)
GTIN	4046356937245
Weight per Piece (including packing)	1.11 g
Weight per Piece (excluding packing)	1.046 g
Customs tariff number	85366990
Country of origin	DE

SF-20KS023 - Crimp contact

1621578

https://www.phoenixcontact.com/in/products/1621578



Technical Data

Connection method	Crimp connection
oduct properties	
Product type	Crimp contact
Contact type	turned
Series	SF
connection data	
Connection method	Crimp connection
Type of contact	Socket
Conductor cross section	2.5 mm ² 4 mm ²
laterial specifications Contact surface	Nickel-plated (Ni), with gold coating (Au)
Contact surface	CuZn
Contact material	Cuzii
imensions	
Mechanical characteristics	
Contact diameter	2 mm
lechanical properties	
Mechanical data	
Insertion/withdrawal cycles	100

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in