



## AZ 15 ZVRK-M16-1762

- Thermoplastic enclosure
- Double-insulated
- Long life
- 52 mm x 75 mm x 30 mm
- Universal coding
- Large wiring compartment
- High level of contact reliability with low voltages and currents
- Slotted holes for adjustment, circular holes for location
- Insensitive to soiling

## Data

### General data

Standards	EN ISO 13849-1 EN ISO 14119 EN IEC 60947-5-1
Coding level according to EN ISO 14119	Low
Working principle	electromechanical
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	100 g

### General data - Features

Number of cable glands	3
Number of safety contacts	1

### Safety classification

Standards	EN ISO 13849-1
-----------	----------------

Mission time 20 Year(s)

### Safety classification - Safety outputs

B<sub>10D</sub> Normally-closed contact (NC) 2,000,000 Operations

### Mechanical data

Mechanical life, minimum 1,000,000 Operations  
Latching force 30 N  
Positive break travel 8 mm  
Positive break force per NC contact, minimum 10 N  
Positive break force, minimum 10 N  
Actuating speed, maximum 2 m/s  
Mounting Screws  
Type of the fixing screws 2x M6

### Mechanical data - Connection technique

Termination Screw terminals  
Cable entry 3 x M16 x 1,5  
Cable section, minimum 0.25 mm<sup>2</sup>  
Cable section, maximum 2.5 mm<sup>2</sup>  
Note (Cable section) All indications including the conductor ferrules.  
Allowed type of cable solid single-wire  
solid multi-wire  
flexible

### Mechanical data - Dimensions

Length of sensor 30 mm  
Width of sensor 52 mm  
Height of sensor 75 mm

## Ambient conditions

Degree of protection	IP67
Ambient temperature	-30 ... +80 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C
Permissible installation altitude above sea level, maximum	2,000 m

## Ambient conditions - Insulation values

Rated insulation voltage $U_i$	500 V
Rated impulse withstand voltage $U_{imp}$	6 kV
Overvoltage category	III
Degree of pollution	3

## Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Switching element	Opener (NC)
Switching principle	slow action, positive break NC contact
Switching frequency	4,000 /h
Material of the contacts, electrical	Silver

## Electrical data - Safety contacts

Voltage, Utilisation category AC-15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	4 A

## Documents

### Operating instructions and Declaration of conformity

AZ 15/16 (411.7 kB, 08/07/2021, W)

## **Operating Instructions and Declaration of Conformity (Short)**

Operating instructions in short form (For further information and languages, see the "Operation and assembly" tab) (389.3 kB, 05/12/2022)

## **CCC certification**

AZ 15 / AZ 16 / AZ 17 / AZ 335 / AZ 355 (1.6 MB, 26/08/2022)

## **SISTEMA-VDMA library**

(659.5 kB, 23/03/2023)

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 27/04/2023, 4:02 am