

# PLC-BPT-120UC/ 1/SEN - Relay base



2900451

<https://www.phoenixcontact.com/in/products/2900451>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



6.2 mm PLC basic terminal block for input functions with push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with sensor supply voltage distribution (BB), 1 N/O contact, input voltage 120 V AC/DC

## Commercial Data

Item number	2900451
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6231
GTIN	4046356512411
Weight per Piece (including packing)	30.99 g
Weight per Piece (excluding packing)	30 g
Customs tariff number	85366990
Country of origin	DE

# PLC-BPT-120UC/ 1/SEN - Relay base



2900451

<https://www.phoenixcontact.com/in/products/2900451>

## Technical Data

### Notes

#### Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

### Product properties

Product type	Relay socket
Product family	PLC-INTERFACE
Application	Input function

### Input data

Nominal input voltage $U_N$	120 V AC/DC
Protective circuit	Bridge rectifier

### Connection data

Connection method	Push-in connection
Stripping length	10 mm
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> (Single ferrule)
	2x 0.5 mm <sup>2</sup> ... 1 mm <sup>2</sup> (TWIN ferrule)
Conductor cross section AWG	26 ... 14

### Dimensions

Width	6.2 mm
Height	80 mm
Depth	94 mm

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

### Approvals

#### Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

### Mounting

Mounting type	DIN rail mounting
Mounting position	any

# PLC-BPT-120UC/ 1/SEN - Relay base

2900451

<https://www.phoenixcontact.com/in/products/2900451>



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)