

# REL-MR-230AC/21HC - Single relay



2961422

<https://www.phoenixcontact.com/in/products/2961422>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 230 V AC

## Your advantages

- RT III-proof (wash-proof)
- Switching current of up to 16 A

## Commercial Data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2961422             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales Key                            | CK6                 |
| Product Key                          | CK6195              |
| Catalog Page                         | Page 290 (C-5-2019) |
| GTIN                                 | 4017918937836       |
| Weight per Piece (including packing) | 16.3 g              |
| Weight per Piece (excluding packing) | 15.89 g             |
| Customs tariff number                | 85364900            |
| Country of origin                    | AT                  |

# REL-MR-230AC/21HC - Single relay



2961422

<https://www.phoenixcontact.com/in/products/2961422>

## Technical Data

### Product properties

|                         |                                 |
|-------------------------|---------------------------------|
| Product type            | Single relay                    |
| Set comprises           | 2834355 PR1-RSC3-LV-230AC/21    |
|                         | 2834436 PR1-RSP3-LV-230AC/21    |
|                         | 2903339 RIF-1-RPT-LV-230AC/1X21 |
|                         | 2903355 RIF-1-RSC-LV-230AC/1X21 |
| Operating mode          | 100% operating factor           |
| Mechanical service life | 1x 10 <sup>7</sup> cycles       |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Pollution degree     | 3   |

### Electrical properties

|   |  |
|---|--|
| Service life electrical                         | see diagram                              |
| Maximum power dissipation for nominal condition | 0.4 W                                    |
| Test voltage (Winding/contact)                  | 5 kV AC (50 Hz, 1 min., winding/contact) |

### Input data

#### Coil side

|                                |  |
|--------------------------------|--|
| Nominal input voltage $U_N$    | 230 V AC                                     |
| Input voltage range            | 179.4 V AC ... 356.5 V AC                    |
| Mains frequency                | 50/60 Hz                                     |
| Typical input current at $U_N$ | 3 mA (50 Hz)                                 |
|                                | 2.5 mA (60 Hz)                               |
| Typical response time          | 3 ms ... 12 ms (depending on phase relation) |
| Typical release time range     | 2 ms ... 9 ms (depending on phase relation)  |
| Coil resistance                | 32500 $\Omega$ $\pm$ 15 % (at 20 °C)         |

### Output data

#### Switching

|                             |                      |
|-----------------------------|----------------------|
| Contact type                | 1 changeover contact |
| Type of switch contact      | Single contact       |
| Drive and function          | monostable           |
| Drive (polarity)            | bipolar              |
| Contact material            | AgNi                 |
| Maximum switching voltage   | 250 V AC/DC          |
| Minimum switching voltage   | 12 V (at 10 mA)      |
| Limiting continuous current | 16 A                 |
| Maximum inrush current      | 25 A (20 ms)         |
| Min. switching current      | 10 mA (at 12 V)      |

# REL-MR-230AC/21HC - Single relay



2961422

<https://www.phoenixcontact.com/in/products/2961422>

|                                       |                                |
|---------------------------------------|--------------------------------|
| Interrupting rating (ohmic load) max. | 384 W (at 24 V DC)             |
|                                       | 58 W (at 48 V DC)              |
|                                       | 48 W (at 60 V DC)              |
|                                       | 50 W (at 110 V DC)             |
|                                       | 80 W (at 220 V DC)             |
|                                       | 4000 VA (for 250 V AC)         |
| Switching capacity                    | 2 A (at 24 V, DC13)            |
|                                       | 0.2 A (at 110 V, DC13)         |
|                                       | 0.2 A (at 250 V, DC13)         |
|                                       | 6 A (at 24 V, AC15)            |
|                                       | 6 A (at 120 V, AC15)           |
|                                       | 6 A (at 250 V, AC15)           |
| Motor load according to UL 508        | 1/2 HP, 120 V AC (N/O contact) |
|                                       | 1 HP, 240 V AC (N/O contact)   |
|                                       | 1/3 HP, 120 V AC (N/C contact) |
|                                       | 3/4 HP, 240 V AC (N/C contact) |
|                                       | 1/4 HP, 200 ... 250 V AC       |

## Connection data

|                   |                          |
|-------------------|--------------------------|
| Connection method | Plug / solder connection |
|-------------------|--------------------------|

## Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 12.7 mm  |
| Height              | 29 mm  |
| Depth               | 15.7 mm  |

## Environmental and real-life conditions

### Ambient conditions

|   |                  |
|---|------------------|
| Degree of protection                    | RT II            |
| Ambient temperature (operation)         | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

## Approvals

### Corrosive gas test

|                |                            |
|----------------|----------------------------|
| Identification | ISA-S71.04. G3 Harsh Group |
|----------------|----------------------------|

# REL-MR-230AC/21HC - Single relay



2961422

<https://www.phoenixcontact.com/in/products/2961422>

|  |               |
|--|---------------|
|  | EN 60068-2-60 |
|--|---------------|

## Standards and regulations

|                       |            |
|-----------------------|------------|
| Standards/regulations | IEC 60664  |
|                       | EN 50178   |
|                       | EN 61810-1 |

## Mounting

|                       |  |
|-----------------------|--|
| Assembly instructions | Can be aligned without spacing ( $> 70\text{ °C} \geq 2.5\text{ mm}$ ) |
| Mounting position     | any  |

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)