


# REL-MR-BL-115AC/21-21 - Single relay



1109569

<https://www.phoenixcontact.com/in/products/1109569>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 115 V AC

## Commercial Data

Item number	1109569
Packing unit	20 pc
Minimum order quantity	20 pc
Sales Key	CK6
Product Key	CK6195
GTIN	4063151021849
Weight per Piece (including packing)	14 g
Weight per Piece (excluding packing)	14 g
Customs tariff number	85364900
Country of origin	AT

## Technical Data

### Product properties

Product type	Single relay
Operating mode	100% operating factor
Mechanical service life	5x 10 <sup>6</sup> cycles

### Insulation characteristics

Insulation	Basic insulation
------------	------------------

### Insulation characteristics

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	3

### Electrical properties

Service life electrical	see diagram
Maximum power dissipation for nominal condition	0.4 W
Test voltage (Winding/contact)	5 kV AC (50 Hz, 1 min., winding/contact)
Rated insulation voltage	250 V AC
Rated surge voltage	4 kV

### Input data

#### Coil side

Nominal input voltage $U_N$	115 V AC
Input voltage range	92 V AC ... 166.8 V AC
Mains frequency	50/60 Hz
Typical input current at $U_N$	6.6 mA
Typical response time	3 ms ... 12 ms (depending on phase relation)
Typical release time range	2 ms ... 9 ms (depending on phase relation)
Coil voltage	115 V AC
Coil resistance	8.1 k $\Omega$ $\pm$ 15 %

### Output data

#### Switching

Contact type	2 changeover contacts
Type of switch contact	Single contact
Drive and function	monostable
Drive (polarity)	bipolar
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V (at 10 mA)
Limiting continuous current	8 A

# REL-MR-BL-115AC/21-21 - Single relay



1109569

<https://www.phoenixcontact.com/in/products/1109569>

Maximum inrush current	12 A (20 ms)
Min. switching current	10 mA (At 5 V)
Interrupting rating (ohmic load) max.	190 W (at 24 V DC)
	85 W (at 48 V DC)
	60 W (at 60 V DC)
	44 W (at 110 V DC)
	60 W (at 220 V DC)
	2000 VA (for 250 V AC)
Switching capacity	2 A (at 24 V, DC13)
	1.5 A (at 230 V, AC15)

## Connection data

Connection method	Plug / solder connection
-------------------	--------------------------

## Dimensions

Dimensional drawing	
Width	12.7 mm
Height	29 mm
Depth	15.7 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	RT II
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

## Standards and regulations

Standards/regulations	IEC 60664
	EN 61810-1

## Mounting

Mounting type	Plug-in mounting
Mounting position	any

# REL-MR-BL-115AC/21-21 - Single relay



1109569

<https://www.phoenixcontact.com/in/products/1109569>

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)